

2.0mm Pin Header

Specifications

- 型態: 180度、90度、SMT
- 電鍍方式: 鍍金、鍍霧錫、鍍亮錫、鍍錫鉛...(鍍層厚度依客戶要求作調整)
- 排數: 單排、雙排、三排、四排
- Pin數: 1x1~1x40 Pin、2x2~2x40 Pin、3x3~3x40 Pin、4x3~4x30 Pin
- 塑膠材質: PBT、NY6T、NY9T (UL 94-V0)
- 塑膠高度: 1.5、2.0mm
- Terminal: Straight、Right Angle、SMT Type
- Plating: Gold、Matte Tin、Bright Tin、Lead Tin ...(The plating model and plating thickness are adjustable as the customer' request)
- Row of pin: Single row、Dual rows、Three rows、Four rows
- Positions: 1x2~1x50 Pin、2x2~2x50 Pin
- Plastic Material: PBT、NY6T、NY9T (UL 94-V0)
- Plastic height: 1.5、2.0mm

Order information

2 0 0 0 1 X 1 X X X X X X X X

(1) (2) (3) (4) (5) (6) (7) (8) (9)

- (1) Pitch: 200=2.00mm
- (2) Series: 01=Pin Header
- (3) Terminal: **S**=Straight Type
R=Right Angle Type / **M**=SMT Type
- (4) 1=Male
- (6) No. Of Positions: 001 to 120
- (7) Plastic Type: A, B, C,...
- (8) Row of Pin: 1=Single Row, 2=Dual Rows
3=Three Rows, 4=Four Rows
- (9) Terminal Dia. Type: 01, 02, 03...

(5)Plating Options:

Full Gold Type	Selective Plated Type(Tin=100μ")	Full Tin(Matte Tin, Bright Tin00")
G:Gold Flash	J:Gold Flash	
E:Gold 1μ"	I:Gold 1μ"	
A:Gold 3μ"	K:Gold 3μ"	
B:Gold 5μ"	L:Gold 5μ"	
C:Gold 10μ"	M:Gold 10μ"	
D:Gold 15μ"	N:Gold 15μ"	
E:Gold 30μ"	P:Gold 30μ"	

Drawing

